Ref. Certif. No.

DK-155431-UL

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product	Linear current sensor
Name and address of the applicant	Chengdu CrossChip Microsystems Co., LTD 4th Floor, 2nd Unit, 3rd Building, No. 88 Tianchen Road,The West High-Tech Zone Chengdu, Sichuan, 611730 China
Name and address of the manufacturer	Chengdu CrossChip Microsystems Co., LTD 4th Floor, 2nd Unit, 3rd Building, No. 88 Tianchen Road,The West High-Tech Zone Chengdu, Sichuan, 611730 China
Name and address of the factory Note: *When more than one factory, please report on page 2*	Shenzhen Mifei Tech Limited Floor 1, 5 And 6, First Building, Able Science Industry District, No.28 Qingfeng Avenuebaolong Street, Longgang District Shenzhen, Guangdong, 518000 China ☐ Additional Information on page 2
Ratings and principal characteristics	(provided for reference only) Maximum working voltage for basic/supplemental insulation: 429V rms or 834Vpk /834VDC. ☒ Additional Information on page 2
Trademark / Brand (if any)	crosschip MicroSystems,Inc.
Customer's Testing Facility (CTF) Stage used	
Model / Type Ref.	CC6937S8-3FByyy, CC6937S8-5FByyy ☒ Additional Information on page 2
Additional information (if necessary may also be reported on page 2)	National Differences: AU, CA, EU Group Differences, JP, NZ, SA, US ☒ Additional Information on page 2
A sample of the product was tested and found to be in conformity with	IEC 62368-1:2018
As shown in the Test Report Ref. No. which forms part of this Certificate	S20240418774101 issued on 2024-07-16

This CB Test Certificate is issued by the National Certification Body

UL Solutions

☐ UL Solutions (US), 333 Pfingsten Rd IL 60062, Northbrook, USA
☒ UL Solutions (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
☐ UL Solutions (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
☐ UL Solutions (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2024-07-22

Signature: Thomas Wilson

Additional Model Detail(s):
CC6937S8-3FByyy, CC6937S8-5FByyy, (“yyy” can be 005 to 075)

Additional Ratings:

Maximum working voltage for reinforced insulation: 214V rms or 417Vpk/417VDC.

Additionally evaluated to:
EN IEC 62368-1:2020, EN IEC 62368-1:2020/A11:2020

Additional information (if necessary)

☐ UL Solutions (US), 333 Pfingsten Rd IL 60062, Northbrook, USA
☒ UL Solutions (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
☐ UL Solutions (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
☐ UL Solutions (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2024-07-22

Signature:

Thomas Wilson